

## Safety Data Sheet



## Section 1: Identification of the Substance/Mixture and of the Company/Undertaking

### 1.1 Product identifier

**Product Name** | MowerGUARD Aerosol  
**Product Code** |

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Relevant identified use(s)** | Dry film lubricant

### 1.3 Details of the supplier of the safety data sheet

**Manufacturer** | Southwestern Graphite  
 (Division of Asbury Carbons)  
 2564 Highway 12  
 DeQuincy, LA 70633  
 (337) 786-5905

Cummings Moore Graphite  
 (Division of Asbury Carbons)  
 1646 N. Green Avenue  
 Detroit, MI 48209  
 (313) 841-1615

### 1.4 Emergency telephone number

**Manufacturer** | **US: 1-800-255-3924; International: +01-813-248-0585; China: 400-120-0751;**  
**Manufacturer** | **Brazil: 0-800-591-6042; India: 000-800-100-4086; Mexico: 01-800-099-0731**  
**ChemTel contract number: MIS0001931 (collect calls accepted)**

## Section 2: Hazards Identification

### EU/EEC

According to: Regulation (EC) No 1272/2008 (CLP)/REACH 1907/2006 [amended by 453/2010]  
 According to: EU Directive 67/548/EEC (DSD) or 1999/45/EC (DPD)

### 2.1 Classification of the substance or mixture

**CLP** | Flammable Aerosols 1 - H222  
 Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects - H336  
 EUH066

**DSD/DPD** | Extremely Flammable (F+)  
 Irritant (Xi)  
 R12, R36, R66, R67

### 2.2 Label Elements

CLP

**DANGER**



**Hazard statements** | H222 - Extremely flammable aerosol.  
 H336 - May cause drowsiness or dizziness

EUH066 - Repeated exposure may cause skin dryness or cracking.

## Precautionary statements

**Prevention** | P210 - Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.  
 P211 - Do not spray on an open flame or other ignition source.  
 P251 - Pressurized container: Do not pierce or burn, even after use.  
 P261 - Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 - Use only outdoors or in a well-ventilated area.

**Response** | P312 - Call a POISON CENTER or doctor/physician if you feel unwell.

**Storage/Disposal** | P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 P405 - Store locked up.  
 P501 - Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## DSD/DPD



**Risk phrases** | R12 - Extremely flammable.  
 R36 - Irritating to eyes.  
 R66 - Repeated exposure may cause skin dryness or cracking.  
 R67 - Vapours may cause drowsiness and dizziness.

**Safety phrases** | S9 - Keep container in a well ventilated place  
 S16 - Keep away from sources of ignition - No Smoking.  
 S26 - In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

## 2.3 Other Hazards

**CLP** | According to Regulation (EC) No. 1272/2008 (CLP) this material is considered hazardous.

**DSD/DPD** | According to European Directive 1999/45/EC this material is considered dangerous.

## United States (US)

According to: OSHA 29 CFR 1910.1200 HCS

### 2.1 Classification of the substance or mixture

**OSHA HCS 2012** | Flammable Aerosols 1  
 Eye Irritation 2  
 Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects  
 Germ Cell Mutagenicity 1B  
 Reproductive Toxicity 2

### 2.2 Label elements

**OSHA HCS 2012**

**DANGER**



**Hazard statements** | Extremely flammable aerosol  
 Causes serious eye irritation  
 May cause drowsiness or dizziness  
 May cause genetic defects.  
 Suspected of damaging fertility or the unborn child.

## Precautionary statements

**Prevention** | Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.  
 Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.  
 Do not spray on an open flame or other ignition source.  
 Pressurized container: Do not pierce or burn, even after use.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.

**Response** | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 Call a POISON CENTER or doctor/physician if you feel unwell.  
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 If eye irritation persists: Get medical advice/attention.  
 IF exposed or concerned: Get medical advice/attention.

**Storage/Disposal** | Store in a well-ventilated place. Keep container tightly closed.  
 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.  
 Store locked up.  
 Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## 2.3 Other hazards

### OSHA HCS 2012

| Under United States Regulations (29 CFR 1910.1200 - Hazard Communication Standard), this product is considered hazardous.

## Canada

According to: WHMIS

## 2.1 Classification of the substance or mixture

### WHMIS

| Flammable Aerosols - B5  
 Other Toxic Effects - D2A  
 Other Toxic Effects - D2B

## 2.2 Label elements

### WHMIS



| Flammable Aerosols - B5  
 Other Toxic Effects - D2A  
 Other Toxic Effects - D2B

## 2.3 Other hazards

### WHMIS

| In Canada, the product mentioned above is considered hazardous under the Workplace Hazardous Materials Information System (WHMIS).

## Section 3 - Composition/Information on Ingredients

### 3.1 Substances

| Material does not meet the criteria of a substance in accordance with Regulation (EC) No 1272/2008.

### 3.2 Mixtures

Composition					
Chemical Name	Identifiers	%	LD50/LC50	Classifications According to Regulation/Directive	Comments
Acetone	<b>CAS:</b> 67-64-1 <b>EC Number:</b> 200-662-2 <b>EU Index:</b> 606-001-00-8	< 45%	Inhalation-Rat LC50 • 50100 mg/m <sup>3</sup> 8 Hour(s) Ingestion/Oral-Rat LD50 • 5800 mg/kg	<b>EU DSD/DPD:</b> Annex VI, Table 3.2: F; R11 Xi; R36 R66 R67 <b>EU CLP:</b> Annex VI, Table 3.1: Flam. Liq. 2, H226; Eye Irrit. 2, H319; STOT SE 3, H336; EUH066 <b>OSHA HCS 2012:</b> Flam. Liq. 2; Eye Irrit. 2; STOT SE 3: Narc.	NDA
Naphtha (petroleum), hydrotreated light	<b>CAS:</b> 64742-49-0 <b>EC Number:</b> 265-151-9 <b>EU Index:</b> 649-328-00-1	10% TO 30%	NDA	<b>EU DSD/DPD:</b> Annex VI, Table 3.2: Carc.Cat.2; R45 Muta.Cat.2; R46 Xn; R65 <b>EU CLP:</b> Annex VI, Table 3.1: Carc. 1B, H350; Muta. 1B, H340; Asp. Tox. 1, H304 <b>OSHA HCS 2012:</b> Not Classified	Contains <0.1% benzene therefore carcinogen and mutagen classifications does not apply.
Graphite	<b>CAS:</b> 7782-42-5 <b>EC Number:</b> 231-955-3	10% TO 25%	NDA	<b>EU DSD/DPD:</b> Not Classified <b>EU CLP:</b> Not Classified <b>OSHA HCS 2012:</b> Comb. Dust	NDA
Propane	<b>CAS:</b> 74-98-6 <b>EC Number:</b> 200-827-9 <b>EU Index:</b> 601-003-00-5	< 25%	NDA	<b>EU DSD/DPD:</b> Annex VI, Table 3.2: F+; R12 <b>EU CLP:</b> Annex VI, Table 3.1: Flam. Gas 1, H220; Press. Gas - Comp., H280 <b>OSHA HCS 2012:</b> Flam. Gas 1; Press. Gas - Comp.; Simp. Asphyx.	NDA
Toluene	<b>CAS:</b> 108-88-3 <b>EC Number:</b> 203-625-9 <b>EU Index:</b> 601-021-00-3	2.4%	Ingestion/Oral-Rat LD50 • 636 mg/kg Inhalation-Rat LC50 • 49 g/m <sup>3</sup> 4 Hour(s) Skin-Rabbit LD50 • 14100 µL/kg	<b>EU DSD/DPD:</b> Annex VI, Table 3.2: F; R11 Xi; R38 Xn; R48/20-65 Repr.Cat.3; R63 R67 <b>EU CLP:</b> Annex VI, Table 3.1: Flam. Liq. 2, H225; Skin Irrit. 2, H315; Repr. 2, H361d; STOT SE 3: Narc., H336; STOT RE 2, H373; Asp. Tox. 1, H304 <b>OSHA HCS 2012:</b> Flam. Liq. 2; Acute Tox. 4 (Oral); Skin Irrit. 2; Eye Irrit. 2; Muta. 1B; Repr. 2; STOT SE 3: Narc.; STOT RE 1 (CNS/Inh); Asp. Tox. 1	NDA
Quartz	<b>CAS:</b> 14808-60-7 <b>EC Number:</b> 238-878-4	< 0.1%	NDA	<b>EU CLP:</b> Community workplace exposure limit <b>OSHA HCS 2012:</b> Exposure limit(s)	NDA

See Section 16 for full text of H-statements and R-phrases.

## Section 4 - First Aid Measures

### 4.1 Description of first aid measures

#### Inhalation

- Move person to fresh air. Administer oxygen if breathing is difficult. Give artificial respiration if victim is not breathing. If signs/symptoms continue, get medical attention.

#### Skin

- Wash skin with soap and water. Wash contaminated clothing before reuse. Get medical attention immediately if symptoms occur.

#### Eye

- In case of contact with substance, immediately flush eyes with running water for at least 20 minutes. If eye irritation persists: Get medical advice/attention.

#### Ingestion

- If swallowed, DO NOT induce vomiting. Get medical attention.

## 4.2 Most important symptoms and effects, both acute and delayed

Refer to Section 11 - Toxicological Information.

## 4.3 Indication of any immediate medical attention and special treatment needed

### Notes to Physician

All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

## Section 5 - Firefighting Measures

### 5.1 Extinguishing media

#### Suitable Extinguishing Media

LARGE FIRE: Water spray, fog or regular foam.  
SMALL FIRES: Dry chemical, CO<sub>2</sub>, water spray or regular foam.

#### Unsuitable Extinguishing Media

No data available

### 5.2 Special hazards arising from the substance or mixture

#### Unusual Fire and Explosion Hazards

Closed containers may explode from internal pressure build-up when exposed to extreme heat and discharge contents.  
Vapors may travel to source of ignition and flash back.  
Vapors may form explosive mixtures with air.  
Overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

#### Hazardous Combustion Products

On burning, may release carbon dioxide and carbon monoxide.

### 5.3 Advice for firefighters

Structural firefighters' protective clothing provides limited protection in fire situations ONLY; it is not effective in spill situations where direct contact with the substance is possible.  
Wear chemical protective clothing that is specifically recommended by the manufacturer. It may provide little or no thermal protection.  
Wear positive pressure self-contained breathing apparatus (SCBA).  
Water may be used to cool containers to prevent pressure build-up and explosion when exposed to extreme heat.

## Section 6 - Accidental Release Measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### Personal Precautions

Ventilate enclosed areas. Do not walk through spilled material. Wear appropriate personal protective equipment, avoid direct contact. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

#### Emergency Procedures

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Keep unauthorized personnel away. Stay upwind. Ventilate closed spaces before entering. Keep out of low areas.

### 6.2 Environmental precautions

Prevent entry into waterways, sewers, basements or confined areas.

### 6.3 Methods and material for containment and cleaning up

#### Containment/Clean-up Measures

Clean up area with absorbent material and place in closed containers for disposal.

### 6.4 Reference to other sections

Refer to Section 8 - Exposure Controls/Personal Protection and Section 13 - Disposal Considerations.

## Section 7 - Handling and Storage

### 7.1 Precautions for safe handling

#### Handling

- ⌋ Keep away from heat and ignition sources – No Smoking. Take precautionary measures against static charges. All equipment used when handling the product must be grounded. Do not puncture or incinerate (burn) cans. Do not stick a pin, nail or any other sharp object into opening on top of can. Use only with adequate ventilation. Use good safety and industrial hygiene practices. Wear appropriate personal protective equipment, avoid direct contact. Do not breathe (dust, vapor or spray mist) Avoid contact with eyes, skin and clothing. Do not use near ignition sources such as sparks or open flames. Do not cut, drill or weld on containers. Even empty containers may contain residue that will support a flame or explode when exposed to a spark, flame or other source of ignition. Do not eat, drink or smoke when using this product. After handling wash hands thoroughly.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage

- ⌋ Store in a cool, dry, well-ventilated place. Keep away from heat, sparks, and flame. Do not store at temperatures >120° F

### 7.3 Specific end use(s)

- ⌋ Refer to Section 1.2 - Relevant identified uses.

## Section 8 - Exposure Controls/Personal Protection

### 8.1 Control parameters

Exposure Limits/Guidelines					
	Result	ACGIH	Europe	NIOSH	OSHA
Quartz (14808-60-7)	TWAs	0.025 mg/m <sup>3</sup> TWA (respirable fraction)	Not established	0.05 mg/m <sup>3</sup> TWA (respirable dust)	Not established
Toluene (108-88-3)	STELs	Not established	100 ppm STEL; 384 mg/m <sup>3</sup> STEL	150 ppm STEL; 560 mg/m <sup>3</sup> STEL	Not established
	TWAs	20 ppm TWA	50 ppm TWA; 192 mg/m <sup>3</sup> TWA	100 ppm TWA; 375 mg/m <sup>3</sup> TWA	200 ppm TWA
	Ceilings	Not established	Not established	Not established	300 ppm Ceiling
Graphite (7782-42-5)	TWAs	2 mg/m <sup>3</sup> TWA (all forms except graphite fibers, respirable fraction)	Not established	2.5 mg/m <sup>3</sup> TWA (natural, respirable dust)	15 mg/m <sup>3</sup> TWA (synthetic, total dust); 5 mg/m <sup>3</sup> TW A (synthetic, respirable fraction)
Propane (74-98-6)	TWAs	1000 ppm TWA (listed under Aliphatic hydrocarbon gases: Alkane C1-4)	Not established	1000 ppm TWA; 1800 mg/m <sup>3</sup> TWA	1000 ppm TWA; 1800 mg/m <sup>3</sup> TWA
Acetone (67-64-1)	TWAs	500 ppm TWA	Not established	250 ppm TWA; 590 mg/m <sup>3</sup> TWA	1000 ppm TWA; 2400 mg/m <sup>3</sup> TWA
	STELs	750 ppm STEL	Not established	Not established	Not established

### Exposure Limits Supplemental

#### OSHA

- Graphite (7782-42-5): **Mineral Dusts:** (15 mppcf TWA (natural))
- Quartz (14808-60-7): **Mineral Dusts:** ((30)/(%SiO<sub>2</sub> + 2) mg/m<sup>3</sup> TWA, total dust; (250)/(%SiO<sub>2</sub> + 5) mppcf TWA, respirable fraction; (10)/(%SiO<sub>2</sub> + 2) mg/m<sup>3</sup> TWA, respirable fraction)

### 8.2 Exposure controls

**Engineering Measures/Controls**

- Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Personal Protective Equipment****Respiratory**

- Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or symptoms are experienced.

**Eye/Face**

- Wear safety goggles.

**Skin/Body**

- Wear protective clothing and gloves.

**Environmental Exposure Controls**

- Controls should be engineered to prevent release to the environment, including procedures to prevent spills, atmospheric release and release to waterways. Follow best practice for site management and disposal of waste.

**Key to abbreviations**

ACGIH = American Conference of Governmental Industrial Hygiene

STEL = Short Term Exposure Limits are based on 15-minute exposures

NIOSH = National Institute of Occupational Safety and Health

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures

OSHA = Occupational Safety and Health Administration

**Section 9 - Physical and Chemical Properties****9.1 Information on Physical and Chemical Properties**

<b>Material Description</b>			
Physical Form	Aerosol	Appearance/Description	Aerosol with a solvent odor.
Color	Data lacking	Odor	Solvent
Odor Threshold	Data lacking		
<b>General Properties</b>			
Boiling Point	Data lacking	Melting Point	Data lacking
Decomposition Temperature	Data lacking	pH	Data lacking
Specific Gravity/Relative Density	Data lacking	Water Solubility	Slightly Soluble
Viscosity	Data lacking	Explosive Properties	Data lacking
Oxidizing Properties:	Data lacking		
<b>Volatility</b>			
Vapor Pressure	Data lacking	Vapor Density	Data lacking
Evaporation Rate	Data lacking		
<b>Flammability</b>			
Flash Point	Data lacking	UEL	Data lacking
LEL	Data lacking	Autoignition	Data lacking
Flammability (solid, gas)	Data lacking		
<b>Environmental</b>			
Octanol/Water Partition coefficient	Data lacking		

**9.2 Other Information**

- No additional physical and chemical parameters noted.

**Section 10: Stability and Reactivity****10.1 Reactivity**

- No dangerous reaction known under conditions of normal use.

## 10.2 Chemical stability

‡ Stable

## 10.3 Possibility of hazardous reactions

‡ Hazardous polymerization will not occur.

## 10.4 Conditions to avoid

‡ Heat, sparks, open flames. Incompatible materials.

## 10.5 Incompatible materials

‡ Strong oxidizing agents, acids, and alkalis.

## 10.6 Hazardous decomposition products

‡ On burning may release carbon dioxide and carbon monoxide.

## Section 11 - Toxicological Information

### 11.1 Information on toxicological effects

		Components
Toluene (2.4%)	108-88-3	<p><b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 636 mg/kg; Inhalation-Rat LC50 • 49 g/m<sup>3</sup> 4 Hour(s); Inhalation-Human TCLo • 1500 mg/m<sup>3</sup> 8 Hour(s); <i>Sense Organs and Special Senses:Eye: Lacrimation; Sense Organs and Special Senses:Eye: Conjunctive irritation; Behavioral: Ataxia;</i> Inhalation-Human TCLo • 200 ppm; <i>Brain and Coverings: Recordings from specific areas of CNS; Behavioral: Antipsychotic; Blood: Changes in bone marrow not included above;</i> Inhalation-Man TCLo • 50 ppm; <i>Kidney, Ureter, and Bladder: Other changes in urine composition;</i> Skin-Rabbit LD50 • 14100 µL/kg;</p> <p><b>Multi-dose Toxicity:</b> Inhalation-Mouse TCLo • 250 ppm 4 Day(s)-Continuous; <i>Behavioral: Convulsions or effect on seizure threshold; Behavioral: Abuse;</i> Inhalation-Mouse TCLo • 50 ppm 12 Week(s)-Intermittent; <i>Brain and Coverings: Other degenerative changes;</i> Inhalation-Rat TCLo • 10 ppm 6 Hour(s) 13 Week(s)-Intermittent; <i>Brain and Coverings: Other degenerative changes; Biochemical: Enzyme inhibition, induction, or change in blood or tissue levels: Multiple enzyme effects;</i></p> <p><b>Mutagen:</b> Micronucleus test • Ingestion/Oral-Mouse • 200 mg/kg; Sister chromatid exchange • Inhalation-Human • 252 µg/L 19 Year(s); Cytogenetic analysis • Inhalation-Rat • 5400 µg/m<sup>3</sup> 16 Week(s)-Intermittent;</p> <p><b>Reproductive:</b> Inhalation-Mouse TCLo • 500 mg/m<sup>3</sup> 24 Hour(s)(6-13D preg); <i>Reproductive Effects: Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus);</i> Inhalation-Mouse TCLo • 200 ppm 7 Hour(s)(7-16D preg); <i>Reproductive Effects: Specific Developmental Abnormalities: Urogenital system</i></p>
Acetone (< 45%)	67-64-1	<p><b>Acute Toxicity:</b> Ingestion/Oral-Rat LD50 • 5800 mg/kg; Inhalation-Rat LC50 • 50100 mg/m<sup>3</sup>;</p> <p><b>Irritation:</b> Eye-Rabbit • 20 mg • Severe irritation; Skin-Rabbit • 395 mg-Open • Mild irritation;</p> <p><b>Reproductive:</b> Inhalation-Rat TCLo • 11000 ppm (6-19D preg); <i>Reproductive Effects: Specific Developmental Abnormalities: Other developmental abnormalities</i></p>

GHS Properties	Classification
Acute toxicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Aspiration Hazard	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Carcinogenicity	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
Germ Cell Mutagenicity	EU/CLP • Data lacking OSHA HCS 2012 • Germ Cell Mutagenicity 1B
Skin corrosion/Irritation	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking



<b>Skin sensitization</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
<b>STOT-RE</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
<b>STOT-SE</b>	EU/CLP • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects OSHA HCS 2012 • Specific Target Organ Toxicity Single Exposure 3: Narcotic Effects
<b>Toxicity for Reproduction</b>	EU/CLP • Data lacking OSHA HCS 2012 • Toxic to Reproduction 2
<b>Respiratory sensitization</b>	EU/CLP • Data lacking OSHA HCS 2012 • Data lacking
<b>Serious eye damage/Irritation</b>	EU/CLP • Data lacking OSHA HCS 2012 • Eye Irritation 2

## Potential Health Effects

### Inhalation

**Acute (Immediate)** | May affect the central nervous system. Symptoms may include dizziness, drowsiness, lethargy, coma and death.

**Chronic (Delayed)** | Repeated and prolonged inhalation may result in impaired lung function.

### Skin

**Acute (Immediate)** | May cause mild irritation.

**Chronic (Delayed)** | Contact may dry the skin prolonged contact may cause irritation. Solvent action can dry and defate the skin causing skin to crack, leading to dermatitis.

### Eye

**Acute (Immediate)** | Causes serious eye irritation.

**Chronic (Delayed)** | No data available

### Ingestion

**Acute (Immediate)** | Under normal conditions of use, no health effects are expected.

**Chronic (Delayed)** | No data available

### Mutagenic Effects

| Repeated and prolonged exposure may cause mutagenic effects.

Carcinogenic Effects			
	CAS	IARC	NTP
Quartz	14808-60-7	Group 1-Carcinogenic	Known Human Carcinogen

**Reproductive Effects** | Animal tests show that Toluene possibly causes toxicity to human reproduction or development.

#### Key to abbreviations

LC = Lethal Concentration

LD = Lethal Dose

T C = Toxic Concentration

## Section 12 - Ecological Information

### 12.1 Toxicity

| Material data lacking.

### 12.2 Persistence and degradability

| Material data lacking.

## 12.3 Bioaccumulative potential

┆ Material data lacking.

## 12.4 Mobility in Soil

┆ Material data lacking.

## 12.5 Results of PBT and vPvB assessment

┆ No PBT and vPvB assessment has been conducted.

## 12.6 Other adverse effects

┆ No studies have been found.

## Section 13 - Disposal Considerations

### 13.1 Waste treatment methods

**Product waste**

┆ Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

**Packaging waste**

┆ Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

## Section 14 - Transport Information

	14.1 UN number	14.2 UN proper shipping name	14.3 Transport hazard class(es)	14.4 Packing group	14.5 Environmental hazards
DOT	NDA	Consumer Commodity, ORM-D	NDA	NDA	NDA
TDG	UN1950	AEROSOLS, FLAMMABLE	2.1	NDA	NDA
IMO/IMDG	UN1950	AEROSOLS, FLAMMABLE	2.1	NDA	NDA
IATA/ICAO	UN1950	Aerosols, flammable	2.1	NDA	NDA

**14.6 Special precautions for user**

┆ None specified.

**14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

┆ Data lacking.

## Section 15 - Regulatory Information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

**SARA Hazard Classifications** ┆ Acute, Chronic, Fire, Pressure(Sudden Release of)

Inventory					
Component	CAS	Canada DSL	Canada NDSL	EU EINECS	EU ELNICS
Acetone	67-64-1	Yes	No	Yes	No
Graphite	7782-42-5	Yes	No	Yes	No
Naphtha (petroleum), hydrotreated light	64742-49-0	Yes	No	Yes	No
Propane	74-98-6	Yes	No	Yes	No

Quartz	14808-60-7	Yes	No	Yes	No
Toluene	108-88-3	Yes	No	Yes	No

## Canada

### Labor

#### Canada - WHMIS - Classifications of Substances

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	B2, D2B
• Propane	74-98-6	A, B1
• Toluene	108-88-3	B2, D2A, D2B D2A (In certain cases, this classification does not apply. For more information, consult the section Substance Specific Issues - Silica, crystalline, encapsulated on Health Canada's WHMIS Division website.)
• Quartz	14808-60-7	
• Graphite	7782-42-5	D2A (natural); D2B (synthetic)

#### Canada - WHMIS - Ingredient Disclosure List

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	1 %
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	1 %
• Quartz	14808-60-7	1 %
• Graphite	7782-42-5	Not Listed

### Environment

#### Canada - CEPA - Priority Substances List

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Priority Substance List 1 (substance not considered toxic)
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

## Europe

### Other

#### EU - Hazardous Substances Restricted or Prohibited in Electrical Equipment (2011/65/EU) (RoHS)

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

## Japan

### Environment

#### Inventory - Japan - Industrial Safety and Health Law Substances (ISHL)

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
---	------------	------------

• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**Other****Japan - Chemical Substance Control Law (CSCL) - Monitoring Chemical Substances**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**Japan - Poisonous and Deleterious Substances - Substances Not Considered Deleterious**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**Japan - Poisonous and Deleterious Substances - Substances Not Considered Poisonous**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**United States****Labor****U.S. - OSHA - Process Safety Management - Highly Hazardous Chemicals**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**U.S. - OSHA - Specifically Regulated Chemicals**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**Environment****U.S. - CAA (Clean Air Act) - 1990 Hazardous Air Pollutants**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed

• Propane	74-98-6	Not Listed
• Toluene	108-88-3	
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed
<b>U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities</b>		
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	5000 lb final RQ; 2270 kg final RQ
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	1000 lb final RQ; 454 kg final RQ
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed
<b>U.S. - CERCLA/SARA - Radionuclides and Their Reportable Quantities</b>		
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed
<b>U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances EPCRA RQs</b>		
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed
<b>U.S. - CERCLA/SARA - Section 302 Extremely Hazardous Substances TPQs</b>		
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed
<b>U.S. - CERCLA/SARA - Section 313 - Emission Reporting</b>		
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	1.0 % de minimis concentration
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed
<b>U.S. - CERCLA/SARA - Section 313 - PBT Chemical Listing</b>		
• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**United States - California****Environment****U.S. - California - Proposition 65 - Carcinogens List**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	carcinogen, initial date 10/1/88 (airborne particles of respirable size)
• Graphite	7782-42-5	Not Listed

**U.S. - California - Proposition 65 - Developmental Toxicity**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	developmental toxicity, initial date 1/1/91
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**U.S. - California - Proposition 65 - Maximum Allowable Dose Levels (MADL)**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	7000 µg/day MADL (level represents absorbed dose)
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**U.S. - California - Proposition 65 - No Significant Risk Levels (NSRL)**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Female**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	female reproductive toxicity, initial date 8/7/09
• Quartz	14808-60-7	Not Listed
• Graphite	7782-42-5	Not Listed

**U.S. - California - Proposition 65 - Reproductive Toxicity - Male**

• Naphtha (petroleum), hydrotreated light	64742-49-0	Not Listed
• Acetone	67-64-1	Not Listed
• Propane	74-98-6	Not Listed
• Toluene	108-88-3	Not Listed
• Quartz	14808-60-7	Not Listed

• Graphite

7782-42-5

Not Listed

## 15.2 Chemical Safety Assessment

| No Chemical Safety Assessment has been carried out.

## 15.3 Other Information

| WARNING: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.

## Section 16 - Other Information

### Relevant Phrases (code & full text)

| H220 - Extremely flammable gas  
| H225 - Highly flammable liquid and vapour  
| H226 - Flammable liquid and vapour  
| H280 - Contains gas under pressure; may explode if heated  
| H304 - May be fatal if swallowed and enters airways  
| H315 - Causes skin irritation  
| H319 - Causes serious eye irritation  
| H340 - May cause genetic defects.  
| H350 - May cause cancer.  
| H361d - Suspected of damaging the unborn child.  
| H373 - May cause damage to organs through prolonged or repeated exposure.  
| R11 - Highly flammable.  
| R38 - Irritating to skin.  
| R45 - May cause cancer.  
| R46 - May cause heritable genetic damage.  
| R48/20 - Harmful: danger of serious damage to health by prolonged exposure through inhalation.  
| R63 - Possible risk of harm to the unborn child.  
| R65 - Harmful: may cause lung damage if swallowed.

### Last Revision Date

| 30/March/2015

### Preparation Date

| 06/22/17

### Disclaimer/Statement of Liability

| The information contained herein is based on data available. However, no warranty is expressed or implied regarding the accuracy of the data or the results obtained from the use thereof. Because the information contained herein may be applied under conditions beyond our control, we assume no responsibility for its use.

### Key to abbreviations

NDA = No data available